

## Insulation Piercing Connectors for ABC cable < 0.6-1 KV >

Main X.L.P.E Cu(Al) self-supporting over head cables to service X.L.P.E Cu(Al) self-supporting over head cable

Manufacture: Delta Electrical Accessories Co.,Ltd  
Item : Insulated insulation piercing connectors



3D Preview

### DA CT 70

**Main:** 35-70 mm<sup>2</sup>, LV ABC  
**Tap:** (6)16-25/35 mm<sup>2</sup>, LV ABC  
Piercing Depth: >=3mm  
Rating Current: 200A  
Exterior Size: 51 x 60 x 87 mm  
Weight: 183 g

#### Feature:

- 1 .High mechanical and weather resistant fire-resistant insulating material body
- 2 .Simultaneous insulation piercing on main and tap.
- 3 .Shear head element:Calibrated part of the tightening system which guaranties the torque recommended by the manufacturer(screw treated against corrosion).
4. seal-cap link.
5. Protection against water(waterproof type).
6. To be supplied with upper and lower washer under the screws from both sides.

bodies in anti UV black resistant thermoplastic fiber glass reinforced

Hot dip galvanzied steel bolt, washer, Nut.  
Shear head in Zice alloy

Connecting bradge in copper tinned ( pure copper or Aluminium should required)

seal compound & Silica gel to improve the water resistance integrity

Couple (Torque) : 13 ± 1 Nm

#### Standard compliant :

NFC33020 UI94 IEC60998-2-3  
GB13140. 4-1998 GB9327. 1-1998 GB9327. 1-1998  
GB9327. 3-1998 GB2317. 3-2000

